

MACHUELOS EN ACERO ALTA VELOCIDAD

NUMÉRICOS

ROSCA AMERICANA 60°

"PUNTA ESPIRAL" o GUN.

CALIDAD DE AJUSTE 2B*

SPIRAL POINTED MACHINE SCREW TAPS

HIGH SPEED STEEL - GROUND THREAD



Codigo	Tamaño	Diam. Nominal en milésimos de pulgada	Longitud total mm	Longitud rosca mm	Diam Vástago mm.	Tamaño Cuadro mm
0103	Nr. 3-48 NC	99	46.00	9.50	3.58	2.79
0104	Nr. 3-56 NF	99	46.00	9.50	3.58	2.79
0105	Nr. 4-36 NS	112	47.60	12.70	3.58	2.79
0106	Nr. 4-40 NC	112	47.60	12.70	3.58	2.79
0107	Nr. 4-48 NF	112	47.60	12.70	3.58	2.79
0108	Nr. 5-40 NC	125	49.20	14.30	3.58	2.79
0109	Nr. 5-44 NF	125	49.20	14.30	3.58	2.79
0110	Nr. 6-32 NC	138	50.80	14.30	3.58	2.79
0111	Nr. 6-40 NF	138	50.80	14.30	3.58	2.79
0112	Nr. 8-32 NC	164	54.00	15.90	4.27	3.33
0113	Nr. 8-36 NF	164	54.00	15.90	4.27	3.33
0114	Nr. 10-24 NC	190	60.30	16.70	4.93	3.86
0115	Nr. 10-32 NF	190	60.30	16.70	4.93	3.86
0116	Nr. 12-24 NC	216	60.30	16.70	5.59	4.19
0117	Nr. 12-28 NF	216	60.30	16.70	5.59	4.19
0118	Nr. 14-20 NS	242	63.50	18.30	6.48	4.85
0119	Nr. 14-24 NS	242	63.50	18.30	6.48	4.85

MACHUELOS EN ACERO ALTA VELOCIDAD

FRACCIONARIOS

"PUNTA ESPIRAL" o Gun.

ROSCA AMERICANA * 60° CALIDAD DE AJUSTE 2B*

SPIRAL POINTED HAND TAPS

HIGH SPEED STEEL - GROUND THREAD

SE SURTEN A SOLICITUD SEGÚN RECOMENDACIONES PARA DIFERENTES CALIDADES DE AJUSTE



Codigo	Tamaño	Diam. Nominal en milésimos de pulgada	Longitud total mm	Longitud rosca mm	Diam Vástago mm.	Tamaño Cuadro mm
0120	1/8-40 NS	3.175	49.210	15.900	3.580	2.790
0121	1/8-44 NS	3.175	49.210	15.900	3.580	2.790
0122	5/32-32 NS	3.960	53.970	19.050	4.260	3.320
0123	5/32-36 NS	3.960	53.970	19.050	4.260	3.320
0124	3/16-24 NS	4.760	60.320	22.200	4.920	3.860
0125	3/16-32 NC	4.760	60.320	22.200	4.920	3.860
0126	7/32-24 NS	5.550	60.320	23.800	5.580	4.190
0127	7/32-32 NS	5.550	60.320	23.800	5.580	4.190
0128	1/4-20 NC	6.350	63.500	18.300	6.480	4.850
0129	1/4-28 NF	6.350	63.500	18.300	6.480	4.850
0130	5/16-18 NC	7.940	69.100	19.800	8.080	6.050
0131	5/16-24 NF	7.940	69.100	19.800	8.080	6.050
0132	3/8-16 NC	9.530	74.600	22.200	9.680	7.260
0133	3/8-24 NF	9.530	74.600	22.200	9.680	7.260
0134	7/16-14 NC	11.110	80.200	25.400	8.200	6.150
0135	7/16-20 NF	11.110	80.200	25.400	8.200	6.150
0136	1/2-13 NC	12.700	85.700	29.400	9.320	6.990
0137	1/2-20 NF	12.700	85.700	29.400	9.320	6.990
0138	5/8-11 NC	15.880	96.800	31.800	12.190	9.140
0139	5/8-18 NF	15.880	96.800	31.800	12.190	9.140
0140	3/4-10 NC	19.050	108.000	35.700	14.990	11.230
0141	3/4-16 NF	19.050	108.000	35.700	14.990	11.230